

Specification		PL-2125
Printing	Print method	Direct thermal line
	Resolution	203DPI
	Print speed	3~5inch/s
	Interface	Serial+USB/Parallel/Ethernet
	Print head	Temperatur sensor: thermal sensitive resistance
		Position sensor: microswith
	Paper presence	Photoelectricity sensor
	Memory	DRAM:2M FLASH:2M
Character Size	FONT O to FONT 8	
	Simplified/Traditional Chinese /Korean	
Barcode	Enlargement&Rotation	1to10 times enlargement in both directions
		0、90、270、360rotation
	Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)
		CODE39/ITF/CODABAR/CODE93/CODE128
Fonts	GB2312	
Media	Media width	20-60mm
	Media diameter	110mm
Power	Cashdrawer out	DC 24V/1A
	Power supply	AC 110V/220V, 50 ~ 60Hz DC 24V/2A
Physical	Weight	1.1kg
properties	Dimension	110 220 160mm
Environment	Work environment	Temperature: 0 ~ 45°C, Humidity: 10 ~ 80%
	Storage environment	Temperature: -10 ~ 60°C, Humidity: 10 ~ 90%
Specification are subject change without notice		

Thermal Direct Label Printer



PL-2125
Resolution : 203dpi